

PCボックスカルバート（150型、300型）形状寸法

呼び寸法	外幅	外高	有効長	厚さ			ハンチ高さ	参考重量
B×H	Bo	Ho	L	T1	T2	T3	C	kg
600 × 600	850	850	2000	125	125	125	100	1920
700 × 700	950	950	2000	125	125	125	100	2170
800 × 800	1050	150	2000	125	125	125	100	2420
900 × 600	1150	850	2000	125	125	125	150	2420
900 × 900	1150	1150	2000	125	125	125	150	2790
1000 × 800	1250	1050	2000	125	125	125	150	2790
1000 × 1000	1250	1250	2000	125	125	125	150	3040
1000 × 1500	1250	1750	2000	125	125	125	150	3660
1100 × 1100	1350	1350	2000	125	125	125	150	3290
1200 × 800	1450	1050	2000	125	125	125	150	3040
1200 × 1000	1450	1250	2000	125	125	125	150	3290
1200 × 1200	1450	1450	2000	125	125	125	150	3540
1200 × 1500	1450	1750	2000	125	125	125	150	3910
1300 × 1300	1550	1550	2000	125	125	125	150	3790
1400 × 1400	1700	1700	2000	150	150	150	150	4880
1500 × 1000	1800	1300	2000	150	150	150	150	4430
1500 × 1200	1800	1500	2000	150	150	150	150	4730
1500 × 1500	1800	1800	2000	150	150	150	150	5180
1800 × 1200	2100	1500	2000	150	150	150	150	5180
1800 × 1500	2100	1800	2000	150	150	150	150	5630
1800 × 1800	2100	2100	2000	150	150	150	150	6080
2000 × 1500	2300	1800	2000	150	150	150	150	5930
2000 × 1800	2300	2100	2000	150	150	150	150	6380
2000 × 2000	2300	23600	2000	150	150	150	150	6680
2200 × 1800	2560	2160	2000	180	180	180	150	8080
2200 × 2200	2560	2560	2000	180	180	180	150	8800
2300 × 1500	2660	1860	2000	180	180	180	150	7710
2300 × 1800	2660	2160	2000	180	180	180	150	8250
2300 × 2000	2660	2360	2000	180	180	180	150	8610
2300 × 2300	2660	2360	2000	180	180	180	150	9150
2400 × 2000	2760	2360	2000	180	180	180	150	8790
2400 × 2400	2760	2760	2000	180	180	180	150	9510
2500 × 1500	2860	1860	2000	180	180	180	150	8070
2500 × 1800	2860	2160	2000	180	180	180	150	8610
2500 × 2000	2860	2360	2000	180	180	180	150	8970
2500 × 2500	2900	2900	2000	200	200	150	150	11030
2800 × 1500	3200	1900	2000	200	200	200	200	9800
2800 × 2000	3200	2400	2000	200	200	200	200	10800
2800 × 2500	3200	2900	2000	200	200	200	200	11800
2800 × 2800	3200	3200	2000	200	200	200	200	12400
3000 × 1500	3400	2000	2000	250	250	200	200	11900
3000 × 2000	3400	2500	2000	250	250	200	200	12900
3000 × 2500	3400	3000	2000	250	250	200	200	13900
3000 × 3000	3500	3500	2000	250	250	250	200	16650
3500 × 2000	4000	2600	2000	300	300	250	300	17900
3500 × 2500	4000	3100	2000	300	300	250	300	19150
4000 × 2000	4500	2600	1500	300	300	250	300	14550
4000 × 2500	4500	3100	1500	300	300	250	300	15490
4500 × 2000	5100	2760	1000	380	380	300	300	13140
4500 × 2500	5100	3260	1000	380	380	300	300	13890
5000 × 2000	5660	2760	1000	380	380	330	300	14510
5000 × 2500	5660	3260	1000	380	380	330	300	15330

* L は有効長であり、製品実長は、目地幅(5mm)を考慮した長さ(L-5mm)とする。

PCボックスカルバート（600型） 形状寸法

呼び寸法	外幅	外高	有効長	厚さ			ハンチ高さ	参考重量
B×H	Bo	Ho	L	T1	T2	T3	C	kg
600 × 600	850	850	2000	125	125	125	100	1920
700 × 700	950	950	2000	125	125	125	100	2170
800 × 800	1050	1050	2000	125	125	125	100	2420
900 × 600	1200	900	2000	150	150	125	150	2700
900 × 900	1200	1200	2000	150	150	125	150	3080
1000 × 800	1300	1100	2000	150	150	150	150	3380
1000 × 1000	1300	1300	2000	150	150	150	150	3680
1000 × 1500	1300	1800	2000	150	150	150	150	4430
1100 × 1100	1400	1400	2000	150	150	150	150	3980
1200 × 800	1500	1100	2000	150	150	150	150	3680
1200 × 1000	1500	1300	2000	150	150	150	150	3980
1200 × 1200	1500	1500	2000	150	150	150	150	4280
1200 × 1500	1500	1800	2000	150	150	150	150	4730
1300 × 1300	1600	1600	2000	150	150	150	150	4580
1400 × 1400	1700	1700	2000	150	150	150	150	4880
1500 × 1000	1800	1300	2000	150	150	150	150	4430
1500 × 1200	1800	1500	2000	150	150	150	150	4730
1500 × 1500	1800	1800	2000	150	150	150	150	5180
1800 × 1200	2160	1560	2000	180	180	180	150	6270
1800 × 1500	2160	1860	2000	180	180	180	150	6810
1800 × 1800	2160	2160	2000	180	180	180	150	7350
2000 × 1500	2400	1900	2000	200	200	200	150	8030
2000 × 1800	2400	2200	2000	200	200	200	150	8630
2000 × 2000	2400	2400	2000	200	200	200	150	9030
2200 × 1800	2660	2260	2000	230	230	230	150	10480
2200 × 2200	2660	2660	2000	230	230	230	150	11400
2300 × 1500	2760	1960	2000	230	230	230	150	10020
2300 × 1800	2760	2260	2000	230	230	230	150	10710
2300 × 2000	2760	2460	2000	230	230	230	150	11170
2300 × 2300	2760	2760	2000	230	230	230	150	11860
2400 × 2000	2900	2500	2000	250	250	250	150	12480
2400 × 2400	2900	2900	2000	250	250	250	150	13480
2500 × 1500	3000	2020	2000	260	260	250	150	11780
2500 × 1800	3000	2320	2000	260	260	250	150	12530
2500 × 2000	3000	2520	2000	260	260	250	150	13030
2500 × 2500	3000	3020	2000	260	260	250	150	14280
2800 × 1500	3360	2060	2000	280	280	280	200	14010
2800 × 2000	3360	2560	2000	280	280	280	200	15410
2800 × 2500	3360	3060	2000	280	280	280	200	16810
2800 × 2800	3360	3360	2000	280	280	280	200	17650
3000 × 1500	3600	2200	2000	350	350	300	200	17500
3000 × 2000	3600	2700	2000	350	350	300	200	19000
3000 × 2500	3600	3200	1500	350	350	300	200	15380
3000 × 3000	3600	3700	1500	350	350	300	200	16500
3500 × 2000	4100	2700	1500	350	350	300	300	15940
3500 × 2500	4100	3260	1500	380	380	300	300	17990
4000 × 2000	4800	2800	1000	400	400	400	300	14050
4000 × 2500	4800	3300	1000	400	400	400	300	15050
4500 × 2000	5300	2900	1000	450	450	400	300	16380
4500 × 2500	5300	3400	1000	450	450	400	300	17380
5000 × 2000	5800	3030	1000	500	530	400	300	19390
5000 × 2500	5800	3530	1000	500	530	400	300	20385

* L は有効長であり、製品実長は、目地幅(5mm)を考慮した長さ(L-5mm)とする。

RCボックスカルバート 形状寸法

呼び寸法		外幅	外高	有効長	厚さ			ハンチ高さ	参考重量
B×H		Bo	Ho	L	T1	T2	T3	C	kg
600	× 600	860	860	2000	130	130	130	100	2000
700	× 700	960	960	2000	130	130	130	100	2260
800	× 800	1060	1060	2000	130	130	130	100	2520
900	× 600	1160	860	2000	130	130	130	100	2390
900	× 900	1160	1160	2000	130	130	130	100	2780
1000	× 800	1260	1060	2000	130	130	130	150	2900
1000	× 1000	1260	1260	2000	130	130	130	150	3160
1000	× 1500	1260	1760	2000	130	130	130	150	3810
1100	× 1100	1360	1360	2000	130	130	130	150	3420
1200	× 800	1460	1060	2000	130	130	130	150	3160
1200	× 1000	1460	1260	2000	130	130	130	150	3420
1200	× 1200	1460	1460	2000	130	130	130	150	3680
1200	× 1500	1460	1760	2000	130	130	130	150	4070
1300	× 1300	1560	1580	2000	140	140	130	150	4100
1400	× 1400	1660	1700	2000	150	150	130	150	4540
1500	× 1000	1780	1320	2000	160	160	140	150	4470
1500	× 1200	1780	1520	2000	160	160	140	150	4750
1500	× 1500	1780	1820	2000	160	160	140	150	5170
1800	× 1200	2100	1540	2000	170	170	150	150	5600
1800	× 1500	2100	1840	2000	170	170	150	150	6050
1800	× 1800	2100	2140	2000	170	170	150	150	6500
2000	× 1500	2320	1860	2000	180	180	160	200	6980
2000	× 1800	2320	2160	2000	180	180	160	200	7460
2000	× 2000	2320	2360	2000	180	180	160	200	7780
2200	× 1800	2560	2200	1500	200	200	180	200	6570
2200	× 2200	2560	2600	1500	200	200	180	200	7110
2300	× 1500	2660	1900	1500	200	200	180	200	6320
2300	× 1800	2660	2200	1500	200	200	180	200	6720
2300	× 2000	2660	2400	1500	200	200	180	200	6990
2300	× 2300	2660	2700	1500	200	200	180	200	7400
2400	× 2000	2780	2420	1500	210	210	190	200	7530
2400	× 2400	2780	2820	1500	210	210	190	200	8100
2500	× 1500	2900	1940	1500	220	220	200	200	7340
2500	× 1800	2900	2240	1500	220	220	200	200	7790
2500	× 2000	2900	2440	1500	220	220	200	200	8090
2500	× 2500	2900	2940	1500	220	220	200	200	8840
2800	× 1500	3240	1980	1000	240	240	220	200	5740
2800	× 2000	3240	2480	1000	240	240	220	200	6290
2800	× 2500	3240	2980	1000	240	240	220	200	6840
2800	× 2800	3240	3280	1000	240	240	220	200	7170
3000	× 1500	3480	2020	1000	260	260	240	300	6770
3000	× 2000	3480	2520	1000	260	260	240	300	7370
3000	× 2500	3480	3020	1000	260	260	240	300	7970
3000	× 3000	3480	3520	1000	260	260	240	300	8570
3500	× 2000	4000	2620	1000	310	310	250	300	9150
3500	× 2500	4000	3120	1000	310	310	250	300	9780

* L は有効長であり、製品実長は、目地幅(5mm)を考慮した長さ(L-5mm)とする。